

PRODUCT SPECIFICATIONS

DVM 4FT



Specifications

DVM 4FT Ku/Ka - Enclosed Satellite Tracking System - Suitable for MEO/GEO Orbits

PHYSICAL DIMENSIONS	62" (Ø) x 54" (H) (Tentative Pending Confirmation)
WEIGHT	TBD
ENVIRONMENTAL	Standardized to IP-65
OPERATING TEMPERATURE	Standard: -40°C - 65°C
PAN/TILT-AXIS RANGE	±217° (PAN) 0° - 120° (TILT)
PAN/TILT-AXIS SPEED	Up to 10°/sec (PAN) Up to 5°/sec (TILT)
SYSTEM TORQUE	50 lb-ft (Counterweighted Avg. - Max 150 lb-ft.)
OPERATING VOLTAGE	24 VDC
OPERATING POWER	Peak: 150 Watts Standby: 10 Watts
CONTROL	BATS Intelligent ICU
LIMITS	Hard and Soft Limits
SLIPRING	No
DUTY CYCLE	100%
POWER CABLING	DC Power Cables, Available up to 330 ft.
CONTROL CABLING	Insulated Instrument Cabling, Available up to 330 ft.
MOUNTING HARDWARE	Custom Mounting Kits Available

Please Note: Final Specifications TBD

 Made In USA


www.batswireless.com
8431 Georgetown Rd. #600
Indianapolis, Indiana 46268

Toll Free +1-888-955-8228
Sales +1-317-500-4507
Support +1-317-500-4506
Email info@batswireless.com