

PRODUCT SPECIFICATIONS

DVM XLIM



Specifications

DVM XLIM - Marine Grade Enclosed Tracking System - (Up to 3FT / 0.9m Antenna)

| | |
|----------------------|--|
| PHYSICAL DIMENSIONS | 52.40" x 55.90" (133 x 141.9 cm) |
| WEIGHT | 220 lbs. (est.) |
| ENVIRONMENTAL | Standardized to IP-66 |
| OPERATING TEMP* | Standard: -40°C - 65°C Optional: -50°C - 65°C |
| OPERATING POWER | Peak: 150 Watts Standby: 10 Watts |
| PAN/TILT-AXIS RANGE* | 360° Continuous (PAN) ±20° (TILT) |
| PAN/TILT-AXIS SPEED | Up to 10°/sec (PAN) Up to 5°/sec (TILT) |
| MOUNTING* | 3" - 4" Pole Mount (Required) |
| OPERATING VOLTAGE | DC: 20 - 50 VDC w/ Autosense 48 VDC Nominal Voltage |
| NETWORK PORTS | (10/100 Mbps) |

Components & Accessories

| | |
|--------------------------|---|
| GPS TARGETING STABILIZER | GPS-Based Signal Targeting & Stabilization |
| FLEET CONTROLLER | Control Appliance for Multiple Control Units |
| POWER CABLING | DC Power Cables, Available up to 330 ft. |
| MIL-SPEC CABLING | Insulated Cat 5e Cabling, Available up to 330 ft. |
| MOUNTING HARDWARE | Universal Pole Mount Kits, Radio Mount Kits |

*Additional Components Required

 Made In USA


www.batswireless.com
8431 Georgetown Rd. #600
Indianapolis, Indiana 46268

Toll Free +1-888-955-8228
Sales +1-317-500-4507
Support +1-317-500-4506
Email info@batswireless.com