

PRODUCT SPECIFICATIONS

DVM VXL IM



Specifications

DVM XIM - Marine Grade Enclosed Tracking System - (Suitable for 4FT Antennas)

PHYSICAL DIMENSIONS	65 x 66.5 in (165.2 x 168.9 cm)
WEIGHT	220 lbs. (99.8 kg)
ENVIRONMENTAL	Standardized to IP-66
OPERATING TEMP*	Standard: -40°C - 65°C Optional: -50°C - 65°C
OPERATING POWER	Peak: 173 Watts Standby: 55 Watts
PAN/TILT-AXIS RANGE*	±217.5° (PAN) ±20° (TILT)
PAN/TILT-AXIS SPEED	Up to 10°/sec (PAN) Up to 5°/sec (TILT)
MOUNTING*	Pedestal Mount (Required)
OPERATING VOLTAGE	DC: 20 - 50 VDC w/Auto Sense (48V Nominal)
NETWORK PORTS	(10/100 Mbps)

Components & Accessories

GPS TARGETING STABILIZER	GPS-Based Signal Targeting & Stabilization
FLEET CONTROLLER	Control Appliance for Multiple Control Units
POWER CABLING	DC Power Cables, Available up to 330 ft.
MIL-SPEC CABLING	Insulated Cat 5e Cabling, Available up to 330 ft.
MOUNTING HARDWARE	Universal Pole Mount Kits, Radio Mount Kits

*Additional Components Required

 Made In USA


www.batswireless.com
8431 Georgetown Rd. #600
Indianapolis, Indiana 46268

Toll Free +1-888-955-8228
Sales +1-317-500-4507
Support +1-317-500-4506
Email info@batswireless.com