

PRODUCT OVERVIEW

FAST 5.8



High Performance Antenna

Ultra-fast (sub- 500ns) antenna array speed through its 24 micro sectors. The solid-state and compact FAST antenna proves ideal for highly-mobile environments where only minimal space is available, such as on a vehicle or small vessel.

Flexible System Deployment

Configurable to allow for both subscriber PTP and PMP network solutions
Allows for the use of 5.6 - 5.9 GHz unlicensed operating frequency.

Unparalleled Outdoor Performance

Broad temperature range, (-30° to 55° C), built to withstand environmental extremes
Sealed, gasketed enclosure mitigates potential water ingress issues. Solid - state design dramatically increases durability, and eliminates potential points of failure due to repeated mechanical movement.

Deep Ecosystem Integration

Developed alongside BATS innovative DVM & BTS product suites, the FAST delivers best-in-class system performance. When paired with suitable partner microwave radios, the FAST aids in faster link acquisition and management; as well as enhanced link stabilization and optimization capabilities.




www.batswireless.com

8431 Georgetown Rd. #600
Indianapolis, Indiana 46268

Toll Free +1-888-955-8228
Sales +1-317-500-4507
Support +1-317-500-4506
Email info@batswireless.com

PRODUCT SPECIFICATIONS

FAST 5.8



Specifications	
FAST 5.8 - Solid State Automated Aiming & Tracking Antenna System	
FREQUENCY	5.6 - 5.9 GHz
PEAK ANTENNA GAIN	16.5 dBi
OMNI MODE / OMNI GAIN	Yes / ~6.5 dBi
ANTENNA GAIN AT CROSSEOVERS	>2 dB Below Peak Gain
POLARIZATION	Dual (Vertical & Horizontal Polarization Available)
SIDELobe ATTENUATION	>18dB (Typical)
BACKLOBE ATTENUATION	>20dB (Typical)
AZIMUTH COVERAGE	360° Cylindrical / Integrated Azimuth Stabilization
AZIMUTH BEAM POSITIONS	24 / <500ns Beam-to-Beam Switch Time
AZIMUTH BEAMWIDTH	40° (Typical @ 5.7 GHz)
ELEVATION BEAMWIDTH	8°
ANTENNA	Passive / 50 Ohms / VSWR 2:1 Typical (2.2:1 Max)
Physical Specifications	
DIMENSIONS	165mm (W) x 712mm (H)
WEIGHT	14 lbs.
ENVIRONMENTAL	IP54 / Operating:-30 to 55°C / Storage:-40 to 70°C
FREQUENCY	5.6 - 5.9 GHz
POWER	18 - 28VDC PoE / 12W (Max)
CONTROL INTERFACE	RS-485 Full Duplex, 57600, 8, 1, Even
POWER AMPLIFIER	Up to 36 dBm Input Power
Testing Specifications	
MIL-STD-810G Method 514.6, Procedure I, Category 20 (Ground Vehicles - Ground Mobile)	
MIL-STD-810G Method 514.6, Procedure IV, Category 20 - Transit Drop	



PRODUCT SPECIFICATIONS

FAST 5.8

